



UniStrip 2550 **Stripping Machine**

- Networking capability
- LED lighting provides the operator with a clear view of the entire working area
- Very sensitive trigger sensor. Works great for small, flexible wires
- Various blade types available
- No mechanical adjustments required when changing wire sizes
- Barcode scanning function

STRIPPING

UniStrip 2550

Application Range | Function

The Schleuniger UniStrip 2550 strips wires ranging in size from 0.03 – 6 mm² (32 – 10 AWG) and jacketed cables up to 5.5 mm (0.22") in diameter. The machine comes standard with V-blades, the optimum solution for stripping most wires without having to change blades. Through the use of special blades, the range of applications can be expanded. Using the color touchscreen, the operator selects the desired wire size from the preprogrammed library and all parameters (cutting diameter, clamping pressure, blade way back, etc.) are automatically set. The operator edits the stripping and pull-off lengths as required and the machine is ready for operation.

Function

The UniStrip 2550 begins the stripping process when the wire end touches the trigger sensor. The wire is automatically clamped and the stripping process is performed according to the programmed values. If desired, the program can be saved to internal memory for future use.

Programmable Processing Parameters

- Cutting diameter and speed
- Blade way back (default values in "Basic Wire", programmable in "Extended Wire")
- Stripping length, pull-off length, pull-off speed
- Trimming function (for precise strip lengths)
- Cable clamping pressure

| Technical specifications | |
|----------------------------|---|
| Conductor Cross-Section | 0.03 – 6 mm ² (32 – 10 AWG) |
| Raw Material Diameter | Maximum 5.5 mm (0.22") |
| Diameter Increments | 0.01 mm (0.001") |
| Strip Length | Minimum 1.5 mm (0.06") With recut: Minimum 0.5 mm (0.02") Maximum 43 mm (1.69") |
| Pull-off Length | Maximum 22 mm (0.86") |
| Strip Length Increments | 0.1 mm (0.01") |
| Cycle Time | 0.35 s (0.75 mm ² (18 AWG) wire, stripping length 10 mm (0.39"), pull-off length 5 mm (0.19")) |
| Cycle Start | Automatic trigger sensor or optional foot pedal |
| Available Stripping Blades | V-blades, Radius-blades, Die-blades, Special blades |
| Raw Material Type | PVC, PUR, rubber, Teflon®, Tefzel®, Kapton, etc. |
| Clamping | Programmable clamping force |
| Memory Capacity | 1000 wires or cables (memory function available only with "Extended Wire") |
| Interfaces | Foot pedal, USB "Host" |
| Options | Foot pedal, special clamping jaws |
| Noise Level | < 70 dB (A) |
| Power Supply | 100/115 VAC, 230/240 VAC, 65 W / 50/60 Hz |
| Dimension (L x W x H) | 390 x 130 x 280 mm (15.3 x 5.1 x 11.0") |
| Weight | 9.4 kg (21 lbs.) |
| CE-Conformity | The UniStrip 2550 fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility. |
| Important Note | Schleuniger recommends that wire samples be submitted in case where there is doubt as to the processing capabilities of a particular machine. |